

SUPERACE® WASHER

SEL-SS type

The industry's first compact, light weight diesel model

The industry's first Diesel Compact High Pressure Washer

- Compact** Can be easily loaded on Truck
- Diesel Engine** Excellent Durability and Superior Safety
- Non-Stop Operation** 25L large fuel tank installed, Max 8 hours non-stop operation
- Lineup** Big flow 30L/min with 20Mpa, can be used for many application

Single Point Hook for lift



Auto Stop device for Dry Run

Large opening Panel for maintenance



Small and Light



Specification	Large Amount of Water	HIGH pressure
Product Name	SEL-3010SS	SEL-1620SS
Code Number	039790	039794
PUMP	Max Pressure(kgf/cm ²)	10.0(102)
	Flow Rate(L/min)	30.0
	RPM	1750
ENGINE	Type	Water-cooled 4-cycle diesel engine
	Total displacement (cc)	479
	Power Rating	7.4kW(10.0PS)/2800min ⁻¹
	Max Power Rating	9.3kW(12.7PS)/3600min ⁻¹
	Starting Method	Cell Starter
	Fuel Type	JIS No.2 light oil (Diesel)
	Tank size (L)	25
Dimensions (LxWxH)(mm)	922x700x850	
Weight(kg)	198.0	

型式名	SEL-3010SS	SEL-1620SS
Equipment	Trigger gun + Spray Lance	
	Straight Nozzle	
	High Pressure Hose 20m	
	Suction Hose 3m	
	Strainer Filter	
	Bypass Hose 3m	

Recommendation

Piping tester T-85

Code no. 03T446

Test for water leakage of the pipe Max Flow Rate: 38.0L/min
Max Pressure: 15.0MPa



High Pressure Power washer